

GP-AC128

5-port full Gigabit intelligent AC server




CE FCC



Introduction

GP-AC128 is a large and medium-sized enterprise gateway based on CAPWAP protocol. It also supports such features as LAN, multi port VPN, multi port network management, multi port VPN Management, multi port network management, multi port network management, multi port VPN, etc+. It is widely used in large and medium-sized enterprises, petroleum and petrochemical, coal mines, villages in cities, hotels, Internet cafes, shopping malls, industrial parks and other places.



Characteristic

- Support line backup
- Multi band superposition
- load balancing
- 5-port full Gigabit Ethernet (up to 4 Wan ports can be configured)
- Diversified access authentication methods
- Support 128 AP management authorization



Hardware performance

| | |
|-------------------------|--------|
| CPU | MT7621 |
| Flash | 128MB |
| DDR | 512MB |
| AP authorization | 128 |
| Largest user | 200+ |



Standards and protocols

| | |
|------------------|---|
| standard | IEEE 802.3, 802.3u, 802.3ab |
| agreement | TCP/IP, DHCP, ICMP, NAT, PPPoE , CAPWAP |



Software function

| | |
|--|---|
| AP management | The maximum number of management users is 200 + users, the number of AP management is 128, centralized and remote management and configuration of wireless AP, and the view of user status |
| Intelligent flow control | One key intelligent flow control, powerful multi line shunt, automatic application priority |
| load balancing | Multi Wan, multi operator access, intelligent load balancing, line backup, network speed overlay |
| 5.8G WiFi transmission protocol | 802.11 a / n / ac |
| device management | Policy Routing: policy, protocol binding and online detection based on source IP address, destination IP address, source MAC address, network interface, domain name, destination port, external network interface, identity binding, etc |
| Routing function | Static routing |
| Behavior management | It also blocks P2P software, P2P flow control and bandwidth allocation, file transmission and URL filtering, and comprehensive control of network behavior |
| Bandwidth control | IP based bandwidth control, guarantee / limit bandwidth, time policy, IP based session restriction |
| Security Center | MAC address filtering, URL / keyword filtering, web content filtering, IP address filtering, port forwarding, DMZ |
| Defense Center | TCP / UDP / ICMP flood prevention, blocking TCP scanning, blocking Ping WAN port |



| | |
|-----------------------|---|
| ARP | Send GARP packet, ARP scan of WAN / LAN port, IP-MAC binding |
| authentication | Local authentication (wechat Wi Fi authentication, SMS authentication, user authentication)Remote authentication (wechat Wi Fi authentication, SMS authentication, user authentication) |
| Administration | Web / cli / telnet Management PortalRemote authentication (wechat Wi Fi authentication, SMS authentication, user authentication) |
| Others | DDNS, VPN |



Interface and power supply

| | |
|-----------------------|---|
| RJ45 interface | 5× Gigabyte LAN |
| Reset | reset (Press and hold for 10 seconds to restore the factory default configuration) |
| POE output | POE48V |
| POE power | The total power of the whole machine is 72W, and the maximum output power of single port Poe is 15.4W |
| power supply | AC |
| Supply voltage | AC220V |



Environmental and physical performance

| | |
|------------------------------------|---|
| working temperature | -30 ~ 60℃ |
| Storage temperature | -40 ~ 80℃ |
| Humidity (non concentrated) | 5% ~ 95% (No condensation) |
| External dimension | 440mm×240mm×44mm(length × width × height) |
| Installation and fixation | Rack type fixed installation |
| Special design | Electromagnetic shielding and fan less cooling design |

